

LEVITON®



Pin & Sleeve Devices

**IEC 60309-1, IEC 60309-2
& Switch-Rated Options**

For North American &
International Applications

TABLE OF CONTENTS

LEV Series	3
ArcArrest® Switch-Rated	20
International Configurations	24
LEV Series Marine Grade	Back Cover



LEV Series

Designed to be stronger and easier to assemble for the most efficient installation and superior performance in any environment.



ArcArrest® Switch-Rated

The simplest and fastest way to de-energize industrial machines and equipment. The local means of disconnect for industrial machinery as required by the NEC and OSHA.



PLUGS & CONNECTORS WITH POWER INDICATION



MECHANICAL INTERLOCKS WITH LOCAL OR REMOTE MONITORING

LEV Series with Award-Winning Inform™ Technology

IIoT solutions for smart manufacturing, enabling safer, more productive operations.



International Configurations

Designed for fast and secure wiring in various IP ratings to meet end-user needs.


LEV Series Configurations

COLOR, NUMBERING AND RATINGS | INDUSTRIAL

North American IEC 60309-1 & IEC 60309-2 Clock Diagram A Guide to Color, Numbering and Ratings


In order to prevent connecting devices to an incorrect power source, the IEC 60309 Standard specifies both physical attributes and marking requirements to prevent such mismatch. The dimensions of the device and ground pin, color of the device, and location of the ground pin are all designed for safety requirements.

Devices are color-coded based on voltage and frequency, and these combinations are distinguished by the location of the ground pin relative to a keyway in the housing. The ground pin can be in one of twelve locations spaced at 30° intervals around the circle on which all the pins lie representing a clock. The various positions are referenced from the view of the open side of a socket (or connector/receptacle); the 6 o'clock (180°) position is at the same angle as the keyway, and is oriented downwards. The ground pin also has a larger diameter than the other pins, preventing the wrong type of plug being inserted into a socket, connector, or receptacle.



Simplify Installation

FASTER ASSEMBLY



Designed with fewer screws to ease assembly

Completely screwless back clamp available for 20/30 Amp devices cuts installation time even further by eliminating 2 additional screws and providing additional dust protection

LEV SERIES



Threaded housing design on plugs and connectors speeds installation



WATCH HOW FAST the LEV Series can be wired and assembled versus competition.



Faster Assembly = Labor and Cost Savings.
CALCULATE NOW!

Simplify Installation

EASIER ASSEMBLY

Mounting feet attachment does not require drilling into the enclosure and can be adjusted for several angles



Bottom hinged cover designed with installer in mind

Captive screws for an easier installation



Receptacles and inlets come with pre-attached gaskets and grounding wires for faster installation

Clearly marked contact carriers offer quick identification of each wire location



Multiple grommets with cord diameter ranges molded-in make it easier to select the correct fit and minimize the risk of compromising a watertight seal



Captive terminal & assembly screws won't fall out during installation or servicing



For Use in Any Environment

SUPERIOR WATERTIGHT RATINGS

LEV SERIES



Withstands any wet and harsh location with the highest and most comprehensive ratings on the market

IP66, IP67, IP68 & IP69K



IP68

- Long-term Submersion



IP69K

High-pressure,
High-temperature
Washdown

For Use in Any Environment

SUPERIOR PERFORMANCE & CONSTRUCTION

Nickel-plated brass pins & sleeves are self-cleaning and corrosion-resistant


No space for debris to build up



NSF Certified sanitary design trusted for use in food & beverage environments



WHAT IS NSF?



Tested to endure impact at the most extreme temperatures

LEV Series: North American Configurations

20, 30, 60 & 100 A Watertight


INDUSTRY
BEST

5
YEAR

LIMITED
WARRANTY

Product Features

- All plugs & connectors and 60 & 100 Amp inlets and receptacles constructed of impact modified nylon. 20 and 30 Amp inlets and receptacles constructed of PBT
- Nickel-plated brass pins and sleeves and stainless steel hardware for added corrosion-resistance
- Plugs & connectors available with alternate screwless clamp (20/30 A only) or power indication with Inform technology
- Watertight and dust-tight rated to IP66, IP67, IP68 and IP69K
- Listed to UL 1682 and 1686, CSA and NOM-ANCE requirements
- NSF certified sanitary design trusted for use in food & beverage facilities
- Meets North American IEC 60309-1 and 60309-2 standards




20 Amp

20 A Watertight Pin & Sleeve Devices

Wiring	Color	Voltage AC	Connector/ Receptacle Clock Position	Plug/ Inlet View	HP Rating	Plug w/Standard Clamp	Plug w/ Alternate Screwless Clamp	Connector w/Standard Clamp	Connector w/ Alternate Screwless Clamp	Receptacle	Inlet
2p3w	Yellow	125	4		—	320P4WLEV	320P4WLEVA	320C4WLEV	320C4WLEVA	320R4WLEV	320B4WLEV
	Blue	250	6		—	320P6WLEV*	320P6WLEVA*	320C6WLEV*	320C6WLEVA*	320R6WLEV*	320B6WLEV*
	Red	480	7		—	320P7WLEV	320P7WLEVA	320C7WLEV	320C7WLEVA	320R7WLEV	320B7WLEV
3p4w	Orange	125/250	12		—	420P12WLEV	420P12WLEVA	420C12WLEV	420C12WLEVA	420R12WLEV	420B12WLEV
	Blue	3Ø250	9		3	420P9WLEV*	420P9WLEVA*	420C9WLEV*	420C9WLEVA*	420R9WLEV*	420B9WLEV*
	Red	3ØY380-415	6		5	420P6WLEV*	—	420C6WLEV*	—	420R6WLEV*	420B6WLEV*
	Red	3Ø480	7		7.5	420P7WLEV	420P7WLEVA	420C7WLEV	420C7WLEVA	420R7WLEV	420B7WLEV
	Black	3Ø600	5		10	420P5WLEV	420P5WLEVA	420C5WLEV	420C5WLEVA	420R5WLEV	420B5WLEV
4p5w	Blue	3ØY120/208	9		2	520P9WLEV*	520P9WLEVA*	520C9WLEV*	520C9WLEVA*	520R9WLEV*	520B9WLEV*
	Red	3ØY200/346-240/415	6		5	520P6WLEV*	—	520C6WLEV*	—	520R6WLEV*	520B6WLEV*
	Red	3ØY277/480	7		7.5	520P7WLEV	520P7WLEVA	520C7WLEV	520C7WLEVA	520R7WLEV	520B7WLEV
	Black	3ØY347/600	5		10	520P5WLEV	520P5WLEVA	520C5WLEV	520C5WLEVA	520R5WLEV	520B5WLEV

* 6 and 9 o'clock positions are dual rated to 16/20 Amp. Custom configurations available upon request.



ORDERING INFORMATION

For LEV Series Pin & Sleeve Devices

4	30	P	7	W	LEV	PI
1 st digit	2 nd , 3 rd or 4 th Digit	Letter	Clock Position*	Suffix	NEW Leviton	Feature
3 = 3 wire	20 = 20 Amp	P = Plug	4 = 4 o'clock	W = Watertight	LEV Series	PI = Power Indication
4 = 4 wire	30 = 30 Amp	C = Connector	5 = 5 o'clock			A = Alternate Screwless Clamp
5 = 5 wire	60 = 60 Amp	R = Receptacle	6 = 6 o'clock			PIA = Power Indication w/ Alternate Screwless Clamp
	100 = 100 Amp	B = Inlet	7 = 7 o'clock			
			9 = 9 o'clock			
			12 = 12 o'clock			

*Clock position applies to ground pin location on female devices

30 Amp

See accessories pages 20-21

30 A Watertight Pin & Sleeve Devices											
Wiring	Color	Voltage AC	Connector/ Receptacle Clock Position	Plug/ Inlet View	HP Rating	Plug w/ Standard Clamp	Plug w/ Alternate Screwless Clamp	Connector w/ Standard Clamp	Connector w/ Alternate Screwless Clamp	Receptacle	Inlet
2p3w	Yellow	125	4		—	330P4WLEV	330P4WLEVA	330C4WLEV	330C4WLEVA	330R4WLEV	330B4WLEV
	Blue	250	6		—	330P6WLEV*	330P6WLEVA*	330C6WLEV*	330C6WLEVA*	330R6WLEV*	330B6WLEV*
	Red	480	7		—	330P7WLEV	330P7WLEVA	330C7WLEV	330C7WLEVA	330R7WLEV	330B7WLEV
3p4w	Orange	125/250	12		—	430P12WLEV	430P12WLEVA	430C12WLEV	430C12WLEVA	430R12WLEV	430B12WLEV
	Blue	3Ø250	9		3	430P9WLEV [†] *	430P9WLEVA [†] *	430C9WLEV [†] *	430C9WLEVA [†] *	430R9WLEV*	430B9WLEV*
	Red	3ØY380-415	6		5	430P6WLEV*	—	430C6WLEV*	—	430R6WLEV*	430B6WLEV*
	Red	3Ø480	7		7.5	430P7WLEV [†]	430P7WLEVA [†]	430C7WLEV [†]	430C7WLEVA [†]	430R7WLEV	430B7WLEV
4p5w	Black	3Ø600	5		10	430P5WLEV	430P5WLEVA	430C5WLEV	430C5WLEVA	430R5WLEV	430B5WLEV
	Blue	3ØY120/208	9		3	530P9WLEV*	530P9WLEVA*	530C9WLEV*	530C9WLEVA*	530R9WLEV*	530B9WLEV*
	Red	3ØY00/346-240/415	6		7.5	530P6WLEV*	—	530C6WLEV*	—	530R6WLEV*	530B6WLEV*
	Red	3ØY277/480	7		10	530P7WLEV	530P7WLEVA	530C7WLEV	530C7WLEVA	530R7WLEV	530B7WLEV
	Black	3ØY347/600	5		15	530P5WLEV	530P5WLEVA	530C5WLEV	530C5WLEVA	530R5WLEV	530B5WLEV

*6 and 9 o'clock positions are Dual Rated to 30/32 Amp. Custom configurations available upon request.

LEV Series Plugs & Connectors with Inform™ Technology

Visual Power Indication for Safety

- Quickly identify if power is present, warning that the device is energized
- Green LEDs will illuminate as a safety precaution
- Allows for faster troubleshooting when there is a power problem with connected equipment

FOR INFORM MODELS:
[†]Add "PI" to end of part number for Power Indication
[°]Change "A" to "PIA" for Power Indication and Alternate Screwless Clamp



LEV Series: North American Configurations

20, 30, 60 & 100 A Watertight

INDUSTRY
BEST

5
YEAR

LIMITED
WARRANTY

Product Features

- All plugs & connectors and 60 & 100 Amp inlets and receptacles constructed of impact modified nylon. 20 and 30 Amp inlets and receptacles constructed of PBT
- Nickel-plated brass pins and sleeves and stainless steel hardware for added corrosion-resistance
- Plugs & connectors available with alternate screwless clamp (20/30 A only) or power indication with Inform technology
- Watertight and dust-tight rated to IP66, IP67, IP68 and IP69K
- Listed to UL 1682 and 1686, CSA and NOM-ANCE requirements
- NSF certified sanitary design trusted for use in food & beverage facilities
- Meets North American IEC 60309-1 and 60309-2 standards



60 Amp

LEV SERIES

60 A Watertight Pin & Sleeve Devices

Wiring	Color	Voltage AC	Connector/ Receptacle Clock Position	Plug/ Inlet View	HP Rating	Plug	Connector	Receptacle	Inlet
2p3w	Yellow	125	⊙ 4	⊙	—	360P4WLEV	360C4WLEV	360R4WLEV	360B4WLEV
	Blue	250	⊙ 6	⊙	—	360P6WLEV*	360C6WLEV*	360R6WLEV*	360B6WLEV*
	Red	480	⊙ 7	⊙	—	360P7WLEV	360C7WLEV	360R7WLEV	360B7WLEV
3p4w	Orange	125/250	⊙ 12	⊙	—	460P12WLEV	460C12WLEV	460R12WLEV	460B12WLEV
	Blue	3Ø250	⊙ 9*	⊙	7.5	460P9WLEV*	460C9WLEV*	460R9WLEV*	460B9WLEV*
	Red	3ØY380-415	⊙ 6*	⊙	10	460P6WLEV*	460C6WLEV*	460R6WLEV*	460B6WLEV*
	Red	3Ø480	⊙ 7	⊙	15	460P7WLEV	460C7WLEV	460R7WLEV	460B7WLEV
	Black	3Ø600	⊙ 5	⊙	20	460P5WLEV	460C5WLEV	460R5WLEV	460B5WLEV
4p5w	Blue	3ØY120/208	⊙ 9*	⊙	5	560P9WLEV*	560C9WLEV*	560R9WLEV*	560B9WLEV*
	Red	3ØY200/346-240/415	⊙ 6*	⊙	10	560P6WLEV*	560C6WLEV*	560R6WLEV*	560B6WLEV*
	Red	3ØY277/480	⊙ 7	⊙	15	560P7WLEV	560C7WLEV	560R7WLEV	560B7WLEV
	Black	3ØY347/600	⊙ 5	⊙	20	560P5WLEV	560C5WLEV	560R5WLEV	560B5WLEV

* 6 and 9 o'clock positions are dual rated to 60/63 Amp.
Custom configurations available upon request.

ORDERING INFORMATION

For LEV Series Pin & Sleeve Devices

4	30	P	7	W	LEV	PI
1 st digit	2 nd , 3 rd or 4 th Digit	Letter	Clock Position*	Suffix	NEW Leviton	Feature
3 = 3 wire	20 = 20 Amp	P = Plug	4 = 4 o'clock	W = Watertight	LEV Series	PI = Power Indication i
4 = 4 wire	30 = 30 Amp	C = Connector	5 = 5 o'clock			A = Alternate Screwless Clamp
5 = 5 wire	60 = 60 Amp	R = Receptacle	6 = 6 o'clock			PIA = Power Indication w/ Alternate Screwless Clamp i
	100 = 100 Amp	B = Inlet	7 = 7 o'clock			
			9 = 9 o'clock			
			12 = 12 o'clock			

*Clock position applies to ground pin location on female devices



100 Amp

100 A Watertight Pin & Sleeve Devices									
Wiring	Color	Voltage AC	Connector/ Receptacle Clock Position	Plug/ Inlet View	HP Rating	Plug	Connector	Receptacle	Inlet
2p3w	Yellow	125	4		—	3100P4WLEV	3100C4WLEV	3100R4WLEV	3100B4WLEV
	Blue	250	6		—	3100P6WLEV*	3100C6WLEV*	3100R6WLEV*	3100B6WLEV*
	Red	480	7		—	3100P7WLEV	3100C7WLEV	3100R7WLEV	3100B7WLEV
3p4w	Orange	125/250	12		—	4100P12WLEV	4100C12WLEV	4100R12WLEV	4100B12WLEV
	Blue	3Ø250	9		10	4100P9WLEV*	4100C9WLEV*	4100R9WLEV*	4100B9WLEV*
	Red	3ØY380-415	6		15	4100P6WLEV*	4100C6WLEV*	4100R6WLEV*	4100B6WLEV*
	Red	3Ø480	7		20	4100P7WLEV	4100C7WLEV	4100R7WLEV	4100B7WLEV
	Black	3Ø600	5		30	4100P5WLEV	4100C5WLEV	4100R5WLEV	4100B5WLEV
4p5w	Blue	3ØY120/208	9		7.5	5100P9WLEV*	5100C9WLEV*	5100R9WLEV*	5100B9WLEV*
	Red	3ØY200/346-240/415	6		20	5100P6WLEV*	5100C6WLEV*	5100R6WLEV*	5100B6WLEV*
	Red	3ØY277/480	7		20	5100P7WLEV	5100C7WLEV	5100R7WLEV	5100B7WLEV
	Black	3ØY347/600	5		30	5100P5WLEV	5100C5WLEV	5100R5WLEV	5100B5WLEV

* 6 and 9 o'clock positions are dual rated to 100/125 Amp. Custom configurations available upon request.

See accessories pages 20-21

Front housing features screwless assembly for plugs and connectors



LEV Series Mechanical Interlocks

EXCLUSIVE INFORM™ TECHNOLOGY



Inform™ is a technology platform that enables Leviton products to provide real-time product data to the end-user. By utilizing smart IIoT solutions, facilities experience safer, more productive operations.

By adding sensors to our devices, users can continually monitor their device health and performance to confirm whether they are working properly. Using advanced analytics, actionable insights are pulled from the sensor data and immediately notify the end-user if there are abnormal operating conditions or a device failure.

LEV Series Mechanical Interlocks with Inform Technology


Enhance Predictive Maintenance Schemes and Deliver Critical Data to the Right Person at the Right Time

LEV Series Mechanical Interlocks with Inform Technology identify disturbances that can impact machine performance and minimize unplanned downtime by monitoring:

- Individual line-side and load-side voltage values
- Ground continuity
- Liquid accumulation inside the enclosure
- Welded contacts




LEV SERIES



Don't let liquid slow you down.

Sensors identify liquid accumulation inside the enclosure and notify you before they can cause a device failure.





LEV Series Mechanical Interlocks

AVAILABLE WITH 24/7 CONDITION MONITORING



Local Monitoring

LED STATES

- Steady GREEN - Normal Operating Condition
- Flashing YELLOW - Warning/Minor Fault
- Flashing RED - Abnormal Operating Condition/Major Fault
- OFF - Normal Power OFF

Remote Monitoring


In addition to local monitoring data, remote monitoring allows for 24/7 access to insights of all devices, such as:

- Enclosure temperature
- Enclosure humidity
- Liquid accumulation
- Line- and load-side voltage values
- Ground continuity
- Support materials

The Inform app offers real-time notifications of abnormal conditions so you can respond faster to potential problems and minimize the duration of downtime events.

EASILY INTEGRATE INTO EXISTING AUTOMATION SYSTEMS

QR code links directly to product detail web page



TAKE A 3D
LOOK INSIDE

The Leviton Inform app is available on:



LEV Series: North American Configurations

20, 30, 60 & 100 A Mechanical Interlocks

INDUSTRY
BEST

5
YEAR

LIMITED
WARRANTY



Product Features

- Impact, UV and chemical-resistant PBT enclosure
- Pre-wired IEC receptacle accepts all manufacturer's IEC 60309-2 plugs
- Fused models accept "Class J" time-delay fuses
- Watertight and dust-tight rated to IP66, IP67, IP68 and IP69K
- NSF certified sanitary design trusted for use in food & beverage facilities
- Meets North American IEC 60309-1 and 60309-2 standards
- Listed to UL 60947-4-1 and 1686, CSA and NOM-ANCE requirements, CE Marked*

See accessories pages 20-21

LEV SERIES

20 A and 30 A Mechanical Interlocks

Amps	Wiring	Color	Voltage AC	Clock Position	Fused Mechanical Interlock	Fused Mechanical Interlock HP Rating	Non-Fused Mechanical Interlock	Non-Fused Mechanical Interlock HP Rating
20	2p3w	Blue	240	6	—	—	320MI6WLEV	3 HP
		Red	480	7	—	—	320MI7WLEV	5 HP
	3p4w	Orange	125/250	12	420MF12WLEV	2 HP @ 120 VAC 3 HP @ 208-240 VAC L-L	420MI12WLEV	2 HP @ 120 VAC 3 HP @ 208-240 VAC L-L
		Blue	3Ø240	9	420MF9WLEV	7.5 HP	420MI9WLEV	10 HP
		Red	3Ø480	7	420MF7WLEV	15 HP	420MI7WLEV	20 HP
	4p5w	Black	3Ø600	5	420MF5WLEV	20 HP	420MI5WLEV	25 HP
		Blue	3ØY120/208	9	—	—	520MI9WLEV	10 HP
		Red	3ØY277/480	7	—	—	520MI7WLEV	20 HP
	30	2p3w	Blue	240	6	—	—	330MI6WLEV
Red			480	7	—	—	330MI7WLEV	10 HP
3p4w		Orange	125/250	12	430MF12WLEV	2 HP @ 120 VAC 3 HP @ 208-240 VAC L-L	430MI12WLEV	2 HP @ 120 VAC 3 HP @ 208-240 VAC L-L
		Blue	3Ø240	9	430MF9WLEV	7.5 HP	430MI9WLEV**	10 HP
		Red	3Ø480	7	430MF7WLEV	15 HP	430MI7WLEV	20 HP
4p5w		Black	3Ø600	5	430MF5WLEV	20 HP	430MI5WLEV	25 HP
		Blue	3ØY120/208	9	—	—	530MI9WLEV	10 HP
		Red	3ØY277/480	7	530MF7WLEV	15 HP	530MI7WLEV	20 HP
4p5w		Black	3ØY347/600	5	530MF5WLEV	20 HP	530MI5WLEV	25 HP

* Non-Inform Only



**430MI9WLEVAC - Available with Factory-Installed Auxiliary Contact

***460MI9WLEVAC - Available with Factory-Installed Auxiliary Contact

Auxiliary Contacts available separately
for all configurations - see page 21

ORDERING INFORMATION

For LEV Series Mechanical Interlocks

4	30	MI	7	W	LEV	C
1 st digit	2 nd , 3 rd or 4 th Digit	Letter	Clock Position*	Suffix	NEW Leviton	Feature
3 = 3 wire	20 = 20 Amp	MI = Mechanical Interlock, Non-Fused	4 = 4 o'clock	W = Watertight	LEV Series	S = Sensing, LED Indication 
4 = 4 wire	30 = 30 Amp	MF = Mechanical Interlock, Fused	5 = 5 o'clock			C = Communicating, Remote Monitoring via Wi-Fi 
5 = 5 wire	60 = 60 Amp 100 = 100 Amp		6 = 6 o'clock 7 = 7 o'clock 9 = 9 o'clock 12 = 12 o'clock	*Clock position applies to ground pin location on female devices		AC = Factory Installed Normally Open (NO) Auxiliary Contact



Features:













- Sensing capabilities
- LED Indication of operating status on cover



Features:


- Sensing capabilities
- LED Indication of operating status on cover
- Remote monitoring via Wi-Fi through the Inform app
- Real-time in-app and email notifications

See accessories pages 20-21

20 A and 30 A Mechanical Interlocks with Inform™ Technology									
Amps	Wiring	Color	Voltage AC	Clock Position	On-device, Local Monitoring		Remote Monitoring via Wi-Fi		
					Non-Fused Mechanical Interlock w/ Sensing	Non-Fused Mechanical Interlock w/ Sensing HP Rating	Non-Fused Mechanical Interlock w/ Communicating	Non-Fused Mechanical Interlock w/ Communicating HP Rating	
20	3p4w	Blue	3Ø240	 9	420MI9WLEVS 	10 HP	420MI9WLEVC 	10 HP	
		Red	3Ø480	 7	420MI7WLEVS 	20 HP	420MI7WLEVC 	20 HP	
30	3p4w	Blue	3Ø240	 9	430MI9WLEVS 	10 HP	430MI9WLEVC 	10 HP	
		Red	3Ø480	 7	430MI7WLEVS 	20 HP	430MI7WLEVC 	20 HP	

ADDITIONAL FEATURES:

1. Embossed ON/OFF markings
2. Strongest handle and interlock design validated through above & beyond endurance testing for improved safety
3. Longer length, overmold handle provides an improved grip and features 3 lockout/tagout provisions for OSHA Compliance
4. Constructed of impact-resistant, UV stable PBT
5. Mounting feet standoff ¼" from surface - Meets NEC® 300.6 air space requirement & NSF Certified



LEV Series: North American Configurations

20, 30, 60 & 100 A Mechanical Interlocks

INDUSTRY
BEST

5
YEAR

LIMITED
WARRANTY



See accessories pages 20-21

Product Features

- Impact, UV and chemical-resistant PBT enclosure
- Pre-wired IEC receptacle accepts all manufacturer's IEC 60309-2 plugs
- Fused models accept "Class J" time-delay fuses
- Watertight and dust-tight rated to IP66, IP67, IP68 and IP69K
- NSF certified sanitary design trusted for use in food & beverage facilities
- Meets North American IEC 60309-1 and 60309-2 standards
- Listed to UL 60947-4-1 and 1686, CSA and NOM-ANCE requirements, CE Marked*

LEV SERIES

60 A and 100 A Mechanical Interlocks								
Amps	Wiring	Colorx	Voltage AC	Clock Position	Fused Mechanical Interlock	Fused Mechanical Interlock HP Rating	Non-Fused Mechanical Interlock	Non-Fused Mechanical Interlock HP Rating
60	2p3w	Blue	240	6	360MF6WLEV	7.5 HP	360MI6WLEV	10 HP
		Red	480	7	—	—	360MI7WLEV	20 HP
	3p4w	Orange	125/250	12	460MF12WLEV	2 HP @ 120 VAC 7.5 HP @ 208-240 VAC L-L	460MI12WLEV	2 HP @ 120 VAC 10 HP @ 208-240 VAC L-L
		Blue	3Ø240	9	460MF9WLEV	15 HP	460MI9WLEV***	20 HP
		Red	3Ø480	7	460MF7WLEV	30 HP	460MI7WLEV	40 HP
	4p5w	Black	3Ø600	5	460MF5WLEV	50 HP	460MI5WLEV	40 HP
		Blue	3ØY120/208	9	560MF9WLEV	15 HP	560MI9WLEV	20 HP
		Red	3ØY277/480	7	—	—	560MI7WLEV	40 HP
		Black	3ØY347/600	5	—	—	560MI5WLEV	40 HP
100	2p3w	Yellow	125	4	—	—	3100MI4WLEV	7.5
		Blue	240	6	—	—	3100MI6WLEV	20 HP
		Red	480	7	—	—	3100MI7WLEV	30 HP
	3p4w	Orange	125/250	12	—	—	4100MI12WLEV	7.5 HP @ 120 VAC 20 HP @ 208-240 VAC L-L
		Blue	3Ø240	9	—	—	4100MI9WLEV	40 HP
		Red	3Ø480	7	—	—	4100MI7WLEV	60 HP
		Black	3Ø600	5	—	—	4100MI5WLEV	50 HP
	4p5w	Blue	3ØY120/208	9	—	—	5100MI9WLEV	40 HP
		Red	3ØY277/480	7	—	—	5100MI7WLEV	60 HP
		Black	3ØY347/600	5	—	—	5100MI5WLEV	50 HP

* Non-Inform Only

**430MI9WLEVAC - Available with Factory-Installed Auxiliary Contact

***460MI9WLEVAC - Available with Factory-Installed Auxiliary Contact

Auxiliary Contacts available separately for all configurations - see page 21

ORDERING INFORMATION

For LEV Series Mechanical Interlocks

4	30	MI	7	W	LEV	C
1 st digit	2 nd , 3 rd or 4 th Digit	Letter	Clock Position*	Suffix	NEW Leviton	Feature
3 = 3 wire	20 = 20 Amp	MI = Mechanical Interlock, Non-Fused	4 = 4 o'clock	W = Watertight	LEV Series	S = Sensing, LED Indication
4 = 4 wire	30 = 30 Amp	MF = Mechanical Interlock, Fused	5 = 5 o'clock			C = Communicating, Remote Monitoring via Wi-Fi
5 = 5 wire	60 = 60 Amp		6 = 6 o'clock			AC = Factory Installed Normally Open (NO) Auxiliary Contact
	100 = 100 Amp		7 = 7 o'clock			
			9 = 9 o'clock			
			12 = 12 o'clock			

*Clock position applies to ground pin location on female devices



See accessories pages 20-21



Features:

- Sensing capabilities
- LED Indication of operating status on cover



Features:

- Sensing capabilities
- LED Indication of operating status on cover
- Remote monitoring via Wi-Fi through the Inform app
- Real-time in-app and email notifications

60 A and 100 A Mechanical Interlocks with Inform™ Technology										
Amps	Wiring	Color	Voltage AC	Clock Position	On-device, Local Monitoring			Remote Monitoring via Wi-Fi		
					Non-Fused Mechanical Interlock w/ Sensing	Non-Fused Mechanical Interlock w/ Sensing HP Rating	Non-Fused Mechanical Interlock w/ Communicating	Non-Fused Mechanical Interlock w/ Communicating HP Rating		
60	3p4w	Blue	3Ø240	9	460MI9WLEVS	20 HP	460MI9WLEVC	20 HP		
		Red	3Ø480	7	460MI7WLEVS	40 HP	460MI7WLEVC	40 HP		
100	3p4w	Blue	3Ø240	9	4100MI9WLEVS	40 HP	4100MI9WLEVC	40 HP		
		Red	3Ø480	7	4100MI7WLEVS	60 HP	4100MI7WLEVC	60 HP		

Replacement Watertight Cap for Connectors and Receptacles

Amperage	Wiring	Cat. No.
20 Amp	3-Wire	CA320LEV
20 Amp	4-Wire	CA420LEV
20 Amp	5-Wire	CA520LEV
30 Amp	3-Wire and 4-Wire	CA343LEV
30 Amp	5-Wire	CA530LEV
60 Amp	All	CA060LEV
100 Amp	All	CA100LEV



Replacement Watertight Locking Ring for Plugs and Inlets

Amperage	Wiring	Device	Cat. No.
20 Amp	3-Wire	Plug	RP320LEV
20 Amp	4-Wire	Plug	RP420LEV
20 Amp	5-Wire	Plug	RP520LEV
30 Amp	3-Wire and 4-Wire	Plug	RP343LEV
30 Amp	5-Wire	Plug	RP530LEV
60 Amp	All	Plugs and Inlets	RA060LEV
100 Amp	All	Plugs and Inlets	RA100LEV
20 Amp	3-Wire	Inlet	RI320LEV
20 Amp	4-Wire	Inlet	RI420LEV
20 Amp	5-Wire	Inlet	RI520LEV
30 Amp	3-Wire and 4-Wire	Inlet	RI343LEV
30 Amp	5-Wire	Inlet	RI530LEV



Replacement Grommets for Plugs and Connectors

Amperage	Cat. No.
20 Amp (6 sizes per bag)	GROM20LEV
30 Amp (6 sizes per bag)	GROM23LEV
60 Amp (7 sizes per bag)	GROM60LEV
100 Amp (6 sizes per bag)	GROM00LEV



Protective Closure Caps for Plugs and Inlets

Amperage	Wiring	Cat. No.
20 Amp	3-Wire	PC320
20 Amp	4-Wire	PC420
20 Amp	5-Wire	PC520
30 Amp	3-Wire and 4-Wire	PC3430
30 Amp	5-Wire	PC530
60 Amp	All	PC60
100 Amp	All	PC100



Watertight Hubs for Mechanical Interlocks and Back Boxes

Die-cast zinc conduit hubs NEMA 4X rated

Size	Wiring
3/4" inch	HUB-34
1 inch	HUB-100
1-1/4" inch	HUB-114
1-1/2" inch	HUB-112
2" inch	HUB-200






Back Boxes		
Amperage	Non-Metallic Cat. No.	Metallic Cat. No.
20/30 Amp	BX230LEV	BX230-M
60 Amp	BX60LEV	BX60-M
100 Amp	BX100LEV	BX100-M



Clamp Assemblies for Plugs and Connectors		
Type	For Use With	Metallic Cat. No.
Wetguard® Style Alternate Screwless Clamp Assembly	20 Amp, 3-Wire and 4-Wire	CLAM2WLEV
Standard Clamp Assembly	20 Amp, 3-Wire and 4-Wire	CLAM20LEV
Wetguard® Style Alternate Screwless Clamp Assembly	20 Amp, 5-Wire and 30 Amp, All	CLAM23WLEV
Standard Clamp Assembly	20 Amp, 5-Wire and 30 Amp, All	CLAM30LEV
Standard Clamp Assembly	60 Amp, All	CLAM60LEV
Standard Clamp Assembly	100 Amp, All	CLAM00LEV



Liquid-Tight Adapters for Plugs & Connectors			
Amperage	Wiring	NPT Size	Cat. No.
20 Amp	3-Wire and 4-Wire	1/2" NPT	SAA12LEV
20/30 Amp	20 Amp 5-Wire and 30 Amp All	1/2" NPT	SAB12LEV
30 Amp	All	3/4" NPT	SAC34LEV
30 Amp	All	1" NPT	SAC10LEV
60 Amp	All	1-1/4" NPT	SAC12LEV
100 Amp	All	1-1/4" NPT	SAD12LEV



Lockout/Tagout for Pin and Sleeve Devices	
Can be used for any IEC 60309-1 and 60309-2 pin and sleeve plugs or inlets	PLG1

Mechanical Interlock and Safety Disconnect Accessories



Mechanical Interlock and Safety Disconnect Accessories	
Cat. No	Description
MOUNT-LDS	Mounting Feet
HNDLE	Replacement Handle
AUXNO	Non-Fused Auxiliary Contact, Rated 10 A 600 V, Normally Open (30/32, 60 and 80 A Devices)
AUXNC-NF	Non-Fused Auxiliary Contact, Rated 10 A 600 V, Normally Closed (30/32, 60 and 80 A Devices)
AUXNC-F1	Fused Auxiliary Contact, Rated 10 A 600 V, Normally Closed (30/32 A Devices)
AUXNO-F1	Fused Auxiliary Contact, Rated 10 A 600 V, Normally Open (30/32 A Devices)
AUXNO-NF1	Non-Fused Auxiliary Contact, Rated 10 A 600 V, Early Break (100 A Devices)
AUXNO-F2	Fused Auxiliary Contact, Rated 10 A 600 V, Normally Open (60 and 100 A Devices)
AUXNC-F2	Fused Auxiliary Contact, Rated 10 A 600 V, Normally Closed (60 and 100 A Devices)
30ASW	30 Amp Non-Fused Replacement Switch
6080A-NF	60/80 Amp Non-Fused Replacement Switch
30ASW-F	30 Amp Fused Replacement Switch
60ASW-F	60 Amp Fused Replacement Switch
100SW-NF	100 Amp Non-Fused Replacement Switch
HUB-34*	3/4" Conduit Hub
HUB-100*	1" Conduit Hub
HUB-114*	1-1/4" Conduit Hub
HUB-112*	1-1/2" Conduit Hub

*Die-cast zinc conduit hubs NEMA 4X rated

ArcArrest® Switch-Rated Pin & Sleeve

ENGINEERED FOR SAFETY, DESIGNED FOR FLEXIBILITY

No exposure to live electrical components or arc flash, even when operating under load


ARCARREST®

Dead front shutter protects users from arc flash and contact with live electrical components

Mounting angle fits on any standard FS/FD Box


Finger drawplates molded into handles for easy connection

Silver tip contact provides multiple advantages, including withstanding wet and corrosive environments, providing low contact resistance even after oxidation and tarnishing, and withstands arcing



ArcArrest® Switch-Rated Pin & Sleeve

MEET UL1682 AND UL2682 REQUIREMENTS
MEET NEC REQUIREMENTS FOR LINE-OF-SIGHT DISCONNECTS



Lockout tagout provisions in both plug and connector allow for fast compliance with OSHA



ArcArrest® Switch-Rated Pin & Sleeve

30 & 60 A

Providing a local means of disconnect as required by NEC, rated for both branch and motor circuit disconnects.

Product Features

- Dead-front safety shutter design contains the arc within the device
- Silver tip contact provides multiple advantages, including withstanding wet and corrosive environments, providing low contact resistance even after oxidation and tarnishing, and withstands arcing
- Marked front and rear contact carrier and insert alignment arrows allow for easy installation
- Housing made of Valox
- 30 A devices feature captive terminal screws for easy installation
- Meet UL1682 and UL2682
- 1-year limited warranty


30 Amp



Plug with Handle and Drawplate shown



Connector with Handle and Drawplate shown



30 A ArcArrest Switch-Rated Pin & Sleeve Devices

Voltage	Polarity	Plug w/ Handle and Drawplate	Plug w/ Handle	Connector w/Handle and Drawplate	Connector w/ Handle	Receptacle	Receptacle w/70° Angle	Inlet	Inlet w/70° Angle
125	1P+N+G	ARC30PD075	ARC30P075	ARC30CD075	ARC30C075	ARC30R075	ARC30RA075	ARC30B075	ARC30BA075
250	2P+G	ARC30PD072	ARC30P072	ARC30CD072	ARC30C072	ARC30R072*	ARC30RA072	ARC30B072*	ARC30BA072
3Ø250	3P+G	ARC30PD073	ARC30P073	ARC30CD073	ARC30C073	ARC30R073*	ARC30RA073	ARC30B073*	ARC30BA073
125/250	2P+N+G	ARC30PD076	ARC30P076	ARC30CD076	ARC30C076	ARC30R076	ARC30RA076	ARC30B076	ARC30BA076
208	2P+G	ARC30PD162	ARC30P162	ARC30CD162	ARC30C162	ARC30R162*	ARC30RA162	ARC30B162*	ARC30BA162
3Ø208	3P+G	ARC30PD163	ARC30P163	ARC30CD163	ARC30C163	ARC30R163*	ARC30RA163	ARC30B163*	ARC30BA163
3ØY120/208	3P+N+G	ARC30PD167	ARC30P167	ARC30CD167	ARC30C167	ARC30R167	ARC30RA167	ARC30B167	ARC30BA167
277	1P+N+G	ARC30PD045	ARC30P045	ARC30CD045	ARC30C045	ARC30R045	ARC30RA045	ARC30B045	ARC30BA045
480	2P+G	ARC30PD042	ARC30P042	ARC30CD042	ARC30C042	ARC30R042*	ARC30RA042	ARC30B042*	ARC30BA042
3Ø480	3P+G	ARC30PD043	ARC30P043	ARC30CD043	ARC30C043	ARC30R043*	ARC30RA043	ARC30B043*	ARC30BA043
3ØY277/480	3P+N+G	ARC30PD047	ARC30P047	ARC30CD047	ARC30C047	ARC30R047	ARC30RA047	ARC30B047	ARC30BA047
600	2P+G	ARC30PD142	ARC30P142	ARC30CD142	ARC30C142	ARC30R142*	ARC30RA142	ARC30B142*	ARC30BA142
3Ø600	3P+G	ARC30PD143	ARC30P143	ARC30CD143	ARC30C143	ARC30R143*	ARC30RA143	ARC30B143*	ARC30BA143
3ØY347/600	3P+N+G	ARC30PD147	ARC30P147	ARC30CD147	ARC30C147	ARC30R147	ARC30RA147	ARC30B147	ARC30BA147

*Add "AC" to end of part number for auxiliary contact versions



Accessories

70° Angle Adapter
ARCANGLE30

Plug/Inlet Cap
ARCPC30

Handle
ARCH30


Handle w/Drawplate
ARCHDP30

ORDERING INFORMATION


For ArcArrest Switch-Rated Pin & Sleeve Devices

ARC	30	PD	07	5
Series	Amperage	Type	Voltage	Phasing
ARC	30 = 30 Amp 60 = 60 Amp	P = Plug and Handle without Drawplate PD = Plug and Handle with Drawplate C = Connector and Handle without Drawplate CD = Connector and Handle with Drawplate R = Female Receptacle RA = Female Receptacle with 70° Angle B = Male Inlet BA = Male Inlet with 70° Angle	16 = 120-127/208-220 07 = 110-125/220-250 04 = 255-277/440-480 14 = 347-600	2 = 2P+G 3 = 3P+G 5 = 1P+N+G 6 = 2P+N+G 7 = 3P+N+G


EXAMPLE:
ARC30PD075
(30 A Plug and Handle with Drawplate, 125V, 1P+N+G)




Position 16
120-127 VAC/208-220 VAC 60 Hz



Position 07
110-125/220-250 VAC 60 Hz



Position 04
255-277 VAC/440-480 VAC 60 Hz



Position 14
347/600 VAC 60 Hz

60 Amp

60 A ArcArrest Switch-Rated Pin & Sleeve Devices

Voltage	Polarity	Plug w/ Handle and Drawplate	Plug w/ Handle	Connector w/ Handle and Drawplate	Connector w/ Handle	Receptacle	Receptacle w/70° Angle	Inlet	Inlet w/70° Angle
125	1P+N+G	ARC60PD075	ARC60P075	ARC60CD075	ARC60C075	ARC60R075	ARC60RA075	ARC60B075	ARC60BA075
250	2P+G	ARC60PD072	ARC60P072	ARC60CD072	ARC60C072	ARC60R072	ARC60RA072	ARC60B072	ARC60BA072
3Ø250	3P+G	ARC60PD073	ARC60P073	ARC60CD073	ARC60C073	ARC60R073	ARC60RA073	ARC60B073	ARC60BA073
125/250	2P+N+G	ARC60PD076	ARC60P076	ARC60CD076	ARC60C076	ARC60R076	ARC60RA076	ARC60B076	ARC60BA076
208	2P+G	ARC60PD162	ARC60P162	ARC60CD162	ARC60C162	ARC60R162	ARC60RA162	ARC60B162	ARC60BA162
3Ø208	3P+G	ARC60PD163	ARC60P163	ARC60CD163	ARC60C163	ARC60R163	ARC60RA163	ARC60B163	ARC60BA163
3ØY120/208	3P+N+G	ARC60PD167	ARC60P167	ARC60CD167	ARC60C167	ARC60R167	ARC60RA167	ARC60B167	ARC60BA167
277	1P+N+G	ARC60PD045	ARC60P045	ARC60CD045	ARC60C045	ARC60R045	ARC60RA045	ARC60B045	ARC60BA045
480	2P+G	ARC60PD042	ARC60P042	ARC60CD042	ARC60C042	ARC60R042	ARC60RA042	ARC60B042	ARC60BA042
3Ø480	3P+G	ARC60PD043	ARC60P043	ARC60CD043	ARC60C043	ARC60R043	ARC60RA043	ARC60B043	ARC60BA043
3ØY277/480	3P+N+G	ARC60PD047	ARC60P047	ARC60CD047	ARC60C047	ARC60R047	ARC60RA047	ARC60B047	ARC60BA047
600	2P+G	ARC60PD142	ARC60P142	ARC60CD142	ARC60C142	ARC60R142	ARC60RA142	ARC60B142	ARC60BA142
3Ø600	3P+G	ARC60PD143	ARC60P143	ARC60CD143	ARC60C143	ARC60R143	ARC60RA143	ARC60B143	ARC60BA143
3ØY347/600	3P+N+G	ARC60PD147	ARC60P147	ARC60CD147	ARC60C147	ARC60R147	ARC60RA147	ARC60B147	ARC60BA147

Accessories

70° Angle Adapter
ARCANGLE60

Plug/Inlet Cap
ARCP60

Handle
ARCH60

Handle w/Drawplate
ARCHDP60

International Configurations

16 A Splashproof

INTERNATIONAL CONFIGURATIONS

Product Features

- Offering includes plugs, connectors, panel mount and surface mount socket outlets, inlets and backboxes
- Available in 16, 32, 63 and 125 Amps
- Ideal for use overseas where voltage and amperage requirements differ from North American standards

Splashproof (IP44) devices features:

- Easy access to wire chambers
- Locking strain relief grip
- Spring clip connection to speed assembly on 16/32 A plugs and connectors
- Rubber gland for watertight seal
- Easily opened, spring-loaded cap on connectors and socket outlets



Splashproof (IP44) Devices



Plug

Connector

Panel Mount
Socket Outlet

Surface Mount
Socket Outlet with
Back Box

Panel Mounting
Inlet

Back Box

Splashproof (IP44) International Rated Devices


















Amps	Poles	Hz	Volts	Connector/ Outlet Clock Position	Plug/ Inlet View	Plug	Connector	Panel Mount Socket Outlet	Surface Mount Socket Outlet w/ Back Box	Panel Mount Inlet	Back Box
16	2P+E (2P, 3W)	50/60Hz	100-130	4		S216-P4	S216-C4	S216-R4	S216-S4	S216-B4	BB16-A
			200-250	6		S216-P6	S216-C6	S216-R6	S216-S6	S216-B6	BB16-A
			380-415	9		S216-P9	S216-C9	S216-R9	S216-S9	S216-B9	BB16-A
	3P+E (3P, 4W)	50/60Hz	200-250	9		S316-P9	S316-C9	S316-R9	S316-S9	S316-B9	BB16-A
			380-415	6		S316-P6	S316-C6	S316-R6	S316-S6	S316-B6	BB16-A
			440-460	11		S316-P11	S316-C11	S316-R11	S316-S11	S316-B11	BB16-A
	3P+N+E (4P, 5W)	50/60Hz	208-250	9		S416-P9	S416-C9	S416-R9	S416-S9	S416-B9	BB16-A
			346-415	6		S416-P6	S416-C6	S416-R6	S416-S6	S416-B6	BB16-A
			440-460	11		S416-P11	S416-C11	S416-R11	S416-S11	S416-B11	BB16-A

ORDERING INFORMATION

For International Configurations

S	4	16	-	C	11
Prefix	Poles (Not Wires)	3rd-5th Digit	Dash	Letter	Clock Position
S = Splashproof	2 = 2 Pole	16 = 16 Amp	-	P = Plug	4 = 4 o'clock
W = Watertight	3 = 3 Pole	32 = 32 Amp	-	C = Connector	6 = 6 o'clock
	4 = 4 Pole	63 = 63 Amp	-	R = Receptacle (Flush Mount Socket Outlet)	9 = 9 o'clock
		125 = 125 Amp	-	S = Surface Mount Receptacle Socket Outlet	11 = 11 o'clock
				B = Inlet	

Splashproof (IP44) International Rated Devices

Amps	Poles	Hz	Volts	Connector/ Outlet Clock Position	Plug/ Inlet View	Plug	Connector	Panel Mount Socket Outlet	Surface Mount Socket Outlet w/ Back Box	Panel Mount Inlet	Back Box
32	2P+E (2P, 3W)	50/60Hz	100-130	 4		S232-P4	S232-C4	S232-R4	S232-S4	S232-B4	BB32-A
			200-250	 6		S232-P6	S232-C6	S232-R6	S232-S6	S232-B6	BB32-A
			380-415	 9		S232-P9	S232-C9	S232-R9	S232-S9	S232-B9	BB32-A
	3P+E (3P, 4W)	50/60Hz	200-250	 9		S332-P9	S332-C9	S332-R9	S332-S9	S332-B9	BB32-A
			380-415	 6		S332-P6	S332-C6	S332-R6	S332-S6	S332-B6	BB32-A
			440-460	 11		S332-P11	S332-C11	S332-R11	S332-S11	S332-B11	BB32-A
	3P+N+E (4P, 5W)	50/60Hz	208-250	 9		S432-P9	S432-C9	S432-R9	S432-S9	S432-B9	BB32-A
			346-415	 6		S432-P6	S432-C6	S432-R6	S432-S6	S432-B6	BB32-A
			440-460	 11		S432-P11	S432-C11	S432-R11	S432-S11	S432-B11	BB32-A

International Configurations

16 A Watertight

INTERNATIONAL CONFIGURATIONS

Product Features

- Offering includes plugs, connectors, panel mount and surface mount socket outlets, inlets and backboxes
- Available in 16, 32, 63 and 125 Amps
- Ideal for use overseas where voltage and amperage requirements differ from North American standards

Watertight (IP66/67) devices features:

- Molded-on gaskets for a trusted watertight seal
- Nickel-plated brass pins and sleeves are corrosion-resistant
- Easy access to wire chambers
- Locking strain relief grip
- Spring clip connection to speed assembly on 16/32 A plugs and connectors
- Rubber gland for watertight seal
- Easily opened, spring-loaded cap on connectors and socket outlets



Watertight (IP66/67) Devices

















































INTERNATIONAL

Watertight (IP66/67) International Rated Devices

Amps	Poles	Hz	Volts	Connector/ Outlet Clock Position	Plug/ Inlet View	Plug	Connector	Panel Mount Socket Outlet	Surface Mount Socket Outlet w/ Back Box	Panel Mount Inlet	Back Box
16	2P+E (2P, 3W)	50/60Hz	100-130	4	4	W216-P4	W216-C4	W216-R4	W216-S4	W216-B4	BB16-A
		50/60Hz	200-250	6	6	W216-P6	W216-C6	W216-R6	W216-S6	W216-B6	BB16-A
		50/60Hz	380-415	9	9	W216-P9	W216-C9	W216-R9	W216-S9	W216-B9	BB16-A
	3P+E (3P, 4W)	50/60Hz	200-250	9	9	W316-P9	W316-C9	W316-R9	W316-S9	W316-B9	BB16-A
		50/60Hz	380-415	6	6	W316-P6	W316-C6	W316-R6	W316-S6	W316-B6	BB16-A
		60Hz	440-460	11	11	W316-P11	W316-C11	W316-R11	W316-S11	W316-B11	BB16-A
	3P+N+E (4P, 5W)	50/60Hz	208-250	9	9	W416-P9	W416-C9	W416-R9	W416-S9	W416-B9	BB16-A
		50/60Hz	346-415	6	6	W416-P6	W416-C6	W416-R6	W416-S6	W416-B6	BB16-A
		60Hz	440-460	11	11	W416-P11	W416-C11	W416-R11	W416-S11	W416-B11	BB16-A

International Configurations

32 A, 63 A, 125 A Watertight

Watertight (IP66/67) International Rated Devices												
Amps	Poles	Hz	Volts	Connector/ Outlet Clock Position	Plug/ Inlet View	Plug	Connector	Panel Mount Socket Outlet	Surface Mount Socket Outlet w/ Back Box	Panel Mount Inlet	Back Box	
32	2P+E (2P, 3W)	50/60Hz	100-130	 4		W232-P4	W232-C4	W232-R4	W232-S4	W232-B4	BB32-A	
		50/60Hz	200-250	 6		W232-P6	W232-C6	W232-R6	W232-S6	W232-B6	BB32-A	
		50/60Hz	380-415	 9		W232-P9	W232-C9	W232-R9	W232-S9	W232-B9	BB32-A	
	3P+E (3P, 4W)	50/60Hz	200-250	 9		W332-P9	W332-C9	W332-R9	W332-S9	W332-B9	BB32-A	
		50/60Hz	380-415	 6		W332-P6	W332-C6	W332-R6	W332-S6	W332-B6	BB32-A	
		60Hz	440-460	 11		W332-P11	W332-C11	W332-R11	W332-S11	W332-B11	BB32-A	
	3P+N+E (4P, 5W)	50/60Hz	208-250	 9		W432-P9	W432-C9	W432-R9	W432-S9	W432-B9	BB32-A	
		50/60Hz	346-415	 6		W432-P6	W432-C6	W432-R6	W432-S6	W432-B6	BB32-A	
		60Hz	440-460	 11		W432-P11	W432-C11	W432-R11	W432-S11	W432-B11	BB32-A	
63	2P+E (2P, 3W)	50/60Hz	200-250	 6		W263-P6	W263-C6	W263-R6	W263-S6	W263-B6	BB63-A	
		50/60Hz	200-250	 9		W363-P9	W363-C9	W363-R9	W363-S9	W363-B9	BB63-A	
	3P+E (3P, 4W)	50/60Hz	380-415	 6		W363-P6	W363-C6	W363-R6	W363-S6	W363-B6	BB63-A	
		60Hz	440-460	 11		W363-P11	W363-C11	W363-R11	W363-S11	W363-B11	BB63-A	
	3P+N+E (4P, 5W)	50/60Hz	208-250	 9		W463-P9	W463-C9	W463-R9	W463-S9	W463-B9	BB63-A	
		50/60Hz	346-415	 6		W463-P6	W463-C6	W463-R6	W463-S6	W463-B6	BB63-A	
		60Hz	440-460	 11		W463-P11	W463-C11	W463-R11	W463-S11	W463-B11	BB63-A	
125	2P+E (2P, 3W)	50/60Hz	200-250	 6		W2125-P6	W2125-C6	W2125-R6	W2125-S6	W2125-B6	BB125-A	
		50/60Hz	200-250	 9		W3125-P9	W3125-C9	W3125-R9	W3125-S9	W3125-B9	BB125-A	
	3P+E (3P, 4W)	50/60Hz	380-415	 6		W3125-P6	W3125-C6	W3125-R6	W3125-S6	W3125-B6	BB125-A	
		60Hz	440-460	 11		W3125-P11	W3125-C11	W3125-R11	W3125-S11	W3125-B11	BB125-A	
	3P+N+E (4P, 5W)	50/60Hz	208-250	 9		W4125-P9	W4125-C9	W4125-R9	W4125-S9	W4125-B9	BB125-A	
		50/60Hz	346-415	 6		W4125-P6	W4125-C6	W4125-R6	W4125-S6	W4125-B6	BB125-A	
		60Hz	440-460	 11		W4125-P11	W4125-C11	W4125-R11	W4125-S11	W4125-B11	BB125-A	


MARINE GRADE

LEV SERIES IEC PIN & SLEEVE DEVICES









KEY FEATURES:

- **Industry-exclusive** - the only manufacturer of ABYC certified Pin & Sleeve devices in the market
- **Marine grade** - withstands harsh, corrosive marine environments
- **Superior watertight ratings** - including IP66/67/68, & IP69K
- **Compatible with Leviton's Marine Grade Power Pedestals** - Rugged, high-quality pedestals featuring power, water, metering, and lighting, all built to your custom specifications.



100 A Lev Series IEC Pin & Sleeve Devices — Marine Grade

Wiring	Voltage AC	Connector/ Receptacle Clock Position	Plug View	Plug	Connector	Receptacle
				YELLOW	YELLOW	GRAY
3p4w	125/250	12 		M4100P12WLEV	M4100C12WLEV	M4100R12WLEV
4p5w	3Ø277/480	7 		M5100P7WLEV	M5100C7WLEV	M5100R7WLEV
	3Ø120/208	9 		M5100P9WLEV	M5100C9WLEV	M5100R9WLEV

Leviton Manufacturing Co., Inc.

201 N Service Rd, Melville, NY 11747

Telephone: 1-800-323-8920 • FAX: 1-800-832-9538

Tech Line (Monday – Friday 8am to 10pm, Saturday 9am to 7pm, Sunday 9am to 5pm - E.S.T.): 1-800-824-3005

Visit our Website at: leviton.com/levseries email: industrial@leviton.com

SCAN TO EXPLORE ALL
PIN & SLEEVE PRODUCT
DETAILS & VIDEOS

